


PRIMA ENVO SERIES

PREMIUM FULLY SYNTHETIC/HIGH PERFORMANCE OILS



Performance Claims

API SN; ACEA C2/C3; MB 229.31/229.51/229.52; BMW LL-04; VW 502 00/505 00/505 01(APPROVED); PORSCHE A-40 (APPROVED); GM DEXOS 2

Product Description

PRIMA ENVO SERIES, are multi-grade engine oils formulated by using the latest in synthetic technology together with the most up to date advancements in additive chemistry and sets new standards in engine oil performance to be provided along with full compatibility with emission control after treatment systems. Mid SAPS (Sulphate ash, Phosphorus and Sulphur) additive technology allows optimum performance of this systems, including particulate filters, which ensures a high level of continuous pollution control thereby minimizing environmental damage.

Features & Benefits

- ✓ Compatible with diesel particulate filters and catalytic converters.
- ✓ Ensures lubricant performance over extended drain intervals.
- ✓ Promotes fuel efficiency savings.
- ✓ Very high standards of engine cleanliness.
- ✓ Exceptional long term anti-wear and oxidation stability.
- ✓ Excellent high and low temperature performance.

Applications

PRIMA ENVO SERIES are particularly suited to vehicles equipped with anti-pollution systems such as diesel/gasoline particulate filters where is mid SAPS levels will greatly prolong the lifetime of the filter. It is also suitable for use in other types of diesel engines as well as petrol engines. Please check your vehicle before use.

Typical Test Data

| Characteristics | Method | Unit | Typical Value | |
|------------------------|-------------|----------|-----------------|-----------------|
| Product Name | | | PRIMA ENVO 5W30 | PRIMA ENVO 5W40 |
| Product Code | | | PVLG49022 | PVLG49023 |
| SAE Grade | | | 5W30 | 5W40 |
| Density @ 25°C | ASTM D 4052 | g/cc | 0.85 | 0.86 |
| K. Viscosity @ 40°C | ASTM D 7042 | cSt | 69.30 | 79.90 |
| K. Viscosity @ 100°C | ASTM D 7042 | cSt | 12.20 | 14.01 |
| CCS. viscosity @ -30°C | ASTM D 5293 | cP | 5500 | 5700 |
| Viscosity Index | ASTM D 2270 | None | 177 | 182 |
| Pour Point, °C | ASTM D 6749 | °C | -39 | -36 |
| Flash Point | ASTM D 92 | °C | 230 | 235 |
| TBN | ASTM D 2896 | mg-KOH/g | 7.5 | 7.5 |

Health and Safety

This product used as our recommendation for intended application is not expected to produce any particular risk. A safety data sheet of the product is available on request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.

Available Packages | BULK | 205 L | 25 L | 20 L | 6X5 L | 4X5 L | 6X4 L | 4X4 L | 12X1L |